























overview

- single or dual supply voltage options
- SPCO or DPCO output relay
- 8 selectable time ranges (0,1sec-100hrs)
- LED indicators for power supply and contact
- 22.5mm DIN rail mount housing or 11pin plug in housing

On delay






On the application of the supply voltage, time delay t commences. At the end of the time delay the output relay pulls in. When the supply voltage is removed the output relay drops out and the time relay resets

ready for the next timing cycle. If the supply voltage ist removed during time t, the output relay will drop out, the unexpired time will be cancelled and the time relay will reset.

Time ranges

	•	•			-	•	
0,1s-	1s-	0,1min-	1min-	0,1h-	1h-	3h-	10h-
1,0s	10s	1min	10min	1h	10h	30h	100h

The time ranges are selected using the DIP switch settings illustrated left, and the required delay time is set using the potentiometer on the front plate.



specification

supply voltage variation	TF7v -1	5 +10% rest -2	20 +10%	
frequency range	TE7x -15+10%; rest -20+10% 48 - 63 Hz			
. , ,				
max. delay time	100%			
repeat accuracy	< 1% of the selected range			
output spec. (EN60947-5-1)				
relay type	1	2	3	
I _e AC-15 230V~	1,5A	1,5A	2,5A	
I _e AC-15 115V~	1,5A	1,5A	2,5A	
I _e DC-13 24V=	1,5A	1,5A	2,5A	
I_{the} @+20°C, detached	8A	10A	10A	
I _{the} @+60°C, attached	5A	5A	5A	
expected life time				
mechanical operations	$1x10^{7}$	1x10 ⁷	1x10 ⁷	
electrical operations	8x10 ⁴	1x10 ⁵	15x10 ⁴	
screws	pozidriv 1, slot 4mm			
screw tightening torque	0,4Nm			
operating conditions	-20 bis +60°C non condensing			

ordering information

part no	supply	7	output	relay type	71.	housing types
TE01+	230V~ / 24V~=	6VA / 1W	DPCO	1	yes	В
TE04+	115V~ / 24V~=	6VA / 1W	DPCO	1	yes	В
DER230+	230V~ / 24V~=	6VA / 1W	SPCO	3	yes	A
DER115+	115V~ / 24V~=	6VA / 1W	SPCO	3	yes	A
TE08+	12V~=	0,7W	SPCO	2	yes	A
TE12+	230V~	6VA	SPCO	2	yes	A
TE13+	24V~=	1 W	SPCO	2	yes	А
TE15+	115V~	6VA	SPCO	2	yes	A
TE41	230V~ / 24V~=	6VA / 1W	DPCO	1	no	G
TE42	230V~ / 24V~=	6VA / 1W	SPCO	1	no	G
TE71	230V \sim w. transf.	2VA	DPCO	1	no	G
TE72	230V \sim w. transf.	2VA	SPCO	1	no	G

other voltages on request

