

# Accupac with electronic charging controller and integrated DC power supply for 24VDC line type LDR40



CE - konform

- Output separated according to VDE 0551
- Extra low safety potential PELV (EN 60204), SELV (EN 60950)
- Overload- and open circuit protected
- With NiCD-accu (LDR40CD24) or NIMH-accu (LDR40MH24)
- Suitable for the tropics - Epoxy resin casted
- Operating status shown by LED
- Safety acc. to VDE, EN, UL, CSA

## Technical data

Input data		
Input voltage AC	85 - 270Volt	0 - 400 Hz
Inputvoltage DC	120Volt - 400Volt	
Input current at nominal load	at 115VAC max. 1,3A / at 230VAC max. 0,65A	
Input current peak	limited for 16A automatic circuit breaker B	
Protective circuit	Transient voltage suppressor Varistor	
Output data		
Output voltage $U_{Nominal}$	see table below	
Output current $I_{Nominal}$	see table below	
Current limiting	-	
Residual ripple (20MHz)	< 25mVpp	
Control data (DC power supply)		
Control deviation load	< 200mV with load variation 10...90%	
Control deviation supply	< 10mV with supply variation $\pm 10\%$	
Control time	< 10 mSek. with load variation 10...90%	
Operating data		
Duty circle	100%	
Operating temperature range	- 20°C to +50°C	
Derating	from 40°C	
Storage temperature range	-30°C...+65°C	
Cooling	selfcooling	
	recommended respective distance 15mm each	
Safety devices		
Fuse for input	3,15Amp. delayed	
Fuse for output	not necessary - cont. short-circuit proof	
Overload protection	integrated into device	
MTBF	>380.000 h	
Safety data		
Test voltage transformer	5 kVac in accordance to VDE 0551	
High voltage resistance	Primary circuit - secondary circuit 3,75 kVac acc. to VDE 0806 / IEC 380	
Degree of EMI suppresion	in acc. to VDE 0871 B, EN 55022/B	
Protection class	Class 1, with PE connection (EN 60950)	
Extra low safety potential	PELV (EN60204), SELV (EN 60950)	
Ambient humidity	95% relative humidity, yearly average dewing allowed for use in tropical ambient	
Protective class enclosure	IP 65	
Protective class terminals	IP 20 (VGB4)	
Vibration proof	>30g at 33Hz in X,Y and Z, acc. to IEC 60068-2-27	
Applied construction regulations		
according to VDE	VDE 0100, 0110, 0113, 0551, 0160/W2, 0806	
IEC	IEC 60950, IEC61000-6-1-2-3-4, IEC60068-2-3	
	IEC 60068-2-11-52, IEC 60529, IEC 380	
EN	EN60950, EN50081-1, EN50081-2, EN50082-1	
	EN61000-6-1-2-3-4, EN50178, EN55022	
	EN55011, EN61000-3-3, EN50204, EN61558-2-13	
	EN60204, EN60529, EN61000-4-2-3-4-5-6-8-11	
	EN60068-1, EN60068-2-1-2-3-6-27-30	
	EN45501, EN50021	
CSA / UL	CSA-C 22.2 / UL60950, UL508, UL1950	
Mechanics		
Mounting	on rail acc. to DIN 46277	



Nominal output voltage		24,0Vdc
Accu-capacity		3,0Ah
Type		LDR40MH24-H
Nominal output current		5,0Amp.
Power		120Watt
Efficiency		89%
Dimensions (W x H x D)		83x161x160,5
Weight		approx. 3,50kg
Order-No.		589930