

9475-ETG

Intrinsically Safe Gigabit Ethernet Dual Port Media Converter

- **Intrinsically Safe ATEX / IECEx Certification**
- **Dual 1310nm Fibre-Optic Ports (10Km)**
- **CPU Management Feature**
- **Dual Port Switch 10/100/1000Mbps LAN (daisy-chain capability)**
- **Fibre-Optic Repeater Mode with 2 Local LAN Ports**
- **Compact dimensions (W: 40 x H: 160 x D: 140 mm)**
- **Ex ia op is IIB T4 Ga, [Ex ia Da] IIIC (non-mining),
Ex ia op is I Ma (M1 mining).**
- **Ta = -40°C to +70°C**
- **Zone 1 / Zone 21 mounting
(Zone 0 / Zone 20 with a suitable Ex ia Power Supply)**



The 9475-ET(G) is an Intrinsically Safe (IS) Dual Port Media Converter Module suitable for Zone 1 / Zone 21 mounting, **(Zone 0 / Zone 20 with a suitable Ex ia Power Supply).**

The use of 1310nm optics (instead of 850nm) allows a longer fibre-optic link length, typically 10Km at (Gigabit) 1000Mbps using Single Mode fibre or 500m when using multi-mode fibre

There are 2x RJ45 (LAN) ports that support 10/100/1000 IS Ethernet connections – these can allow ‘daisy-chaining’ of units together.

Power (12V DC) is supplied to the module locally.

The compact and cost effective design makes it the ideal choice for many applications:

- Petrochem -** Process Monitoring, Galvanic Isolation...
- Mining -** Underground Communication Links, Machine Monitoring....

Electrical connections are via cage-clamp and/or screw type plug/socket terminals along with RJ45 type connectors for the Ethernet LAN ports. The Fibre ports are duplex SC type.

9475-ETG

April 2020

DRAFT - 23th April 2020

SPECIFICATION

Power supplies

12VDC IS Power Supply Input
Typically 12V @ 270mA
U_i = 15.4V
9492-PS-PLUS recommended

Ethernet

Intrinsically Safe 10/100/1000Base-T

Connector

RJ45 (x2)

Cable Length

Up to 100m Cat5e

FIBRE OPTIC CONNECTIONS

Connector (Top Port TX, Bottom Port RX)

Duplex SC (Gigabit 1000Mbps single-mode or multi-mode)
1000BASE-X

SAFETY

Eye Safety

Class 1 LED/Laser Product

Location of Unit

Zone 1, IIB T4 hazardous area

Certification Code

Ex ia op is IIB T4 Ga
[Ex ia Da] IIIC T135°C (non-mining)
Ex ia op is I Ma (M1 mining)
Ta = -40°C to +70°C

Certificate numbers

CML 19ATEX2414X
IECEX CML 19.0150X
IECEX (QLD pending)

See certificates for further information

ENVIRONMENTAL

Operating Temperature

-40°C...+70°C

Storage Temperature

-40°C...+70°C

Humidity

0...95% RH, non-condensing

Ingress Protection

Select enclosure to suit application,
see certificates for information

MECHANICAL

Width	40mm
Height	160mm
Depth	140mm
Weight	1500g
Mounting	Din Rail

LED INDICATORS

	OFF	FLASH	ON
PWR (green)	Power Fail	N/A	Power OK
WDG (red/green)	Fault	Green - Healthy (10Hz)	Fault
STAT (red/green)	N/A	Green – Identify module mode	Red (fault) Green (healthy)
RJ45 ACT (yellow)	Ethernet link disconnected	Ethernet link activity	Ethernet link connected
RJ45 1000 (green)	10/100Mbps	N/A	1000Mbps
FIBRE Ports (purple)	No Link	Data	Linked

FIBRE PORT SPECIFICATION (Gigabit)

1000BASE-X

TX Output (1310nm)

Single-Mode -9.5dBm (min), -3dBm (max) *note1

RX Sensitivity

Single-Mode -21dBm (max)

*note1 – transmit power coupled into 9um single-mode fibre

DATA & POWER TERMINALS

Power & External LEDs (CON1)

Pin	Function	Pin	Function
1	Power In +12V	2	Power In 0V
3		4	
5		6	
7		8	
9		10	
11	0V	12	0V
13	LAN1 LED	14	LAN2 LED
15	FIBRE1 LED	16	FIBRE2 LED
17		18	

LAN (RJ45) 10/100/1000 BASE-T Ethernet

Pin	Gigabit Function
1	BI_DA+
2	BI_DA-
3	BI_DB+
4	BI_DC+
5	BI_DC-
6	BI_DB-
7	BI_DD+
8	BI_DD-

- LEDS wire between LED terminal and 0V (no resistor required)

ORDERING INFORMATION

Part Number	Description	Comments
9475-ETG	Dual Media Converter – 1000Mbps Gigabit Single/Multi-Mode SC	Standard



SENSE | MONITOR | CONTROL

(02) 4964 4022

www.automatedcontrol.com.au



Eaton Electric Limited,
Great Marlings, Butterfield, Luton
Beds, LU2 8DL, UK.
Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283
E-mail: mtlenquiry@eaton.com
www.mtl-inst.com

© 2020 Eaton
All Rights Reserved
Publication No. 9475-ETG Rev 2 230420
April 2020

EUROPE (EMEA):
+44 (0)1582 723633
mtlenquiry@eaton.com

THE AMERICAS:
+1 800 835 7075
mtl-us-info@eaton.com

ASIA-PACIFIC:
+65 6 645 9888
sales.mtlsing@eaton.com

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.